

CDR Mediation Server

—○ Datasheet

The Mr. Magic of records

The TELES CDR Mediation Server morphs Call Detail Records into data for billing and multiple down-stream applications. The CDR Mediation Server collects raw CDRs recorded on the TELES Softswitches, parses, correlates, mediates and finally transfers them to the external billing system. Billing records are mediated into any output format required by the external application.

The sophisticated TELES CDR Mediation Server comes with a browser-based GUI for mediation configuration and is integrated in the TELES EMS for monitoring and alarm management.

BENEFITS AT A GLANCE

- In-depth mediation and aggregation of Call Detail Records (CDR) from one or more CDR sources
- Various output streams for multiple billing targets
- High CDR throughput
- Fast and direct link to the billing process
- Web-based configuration

CDR Mediation Server	
Performance	
CDR Processing (CDRs per day)	up to 40 Mio
Call Controllers / Call Engines	16 / 32
Output streams	32
Output formats	32
Supported Softswitch versions	
3.7 and 4	
Supported CDR formats	
32, 33, 34, 35, and 36	
Management	
EMS GUI, CLI	☉
Monitoring	
SNMPv2 standard MIBs	☉
Hypervisor / Operating System	
VMware ESXi 6.5 or later; CentOS 7	

TELES AG Informationstechnologien
 Ordensmeisterstr. 15-16
 12099 Berlin
 Germany

T +49 (30) 399 28 00
 F +49 (30) 399 28 01
 contact@teles.com

www.teles.com